



## Winding Ohmmeter RMO50M

- Lightweight - only 8 kg
- Test current 5 mA – 50 A DC
- Measuring range 0,1  $\mu\Omega$  - 1000  $\Omega$
- Mechanical protection IP43
- Extremely quick measurement



### High DC current resistance meter for motors/generators

#### Description

The Winding Ohmmeter RMO50M is designed for winding resistance measurement of electrical motors and generators. RMO50M generates true ripple free DC current. The test result is displayed as  $R=U/I$ .

The RMO50M instrument can store up to 100 measurements. All measurements are time and date stamped. Using RMOWin-M software a test can be performed from a PC, and the results can be obtained directly at a PC. Using RMOWin-M the result can be arranged as an Excel spreadsheet which can be later shown as a diagram and printed for a report. The RMO50M has very high ability to cancel electrostatic and electromagnetic interference in HV electric fields. It is achieved by very efficient filtration. The filtration is made utilizing proprietary hardware and software.

#### Typical application

Typical application of RMO50M is measuring the resistance of:

- ✓ Generators and electrical motors
- ✓ High-current busbar joints
- ✓ Cable splices

#### Recommended accessories

- ✓ RMOWin-M PC software including USB cable
- ✓ Mains power cable
- ✓ Ground (PE) cable

#### Optional accessories

- ✓ Sense cables 2 x 5 m 2,5 mm<sup>2</sup>
- ✓ Current cables 2 x 5 m 10 mm<sup>2</sup>
- ✓ Built-in thermal printer
- ✓ Test shunt 150 A / 150 mV
- ✓ Current cables 2 x 10 m 10 mm<sup>2</sup>
- ✓ Sense cables 2 x 10 m 2,5 mm<sup>2</sup>
- ✓ Transport bags
- ✓ Transport case

## Technical data

### 1 - Mains Power Supply

- Connection according to IEC/EN60320-1; UL498, CSA 22.2
- Voltage single phase 110 V – 240 V AC, +10% - -15%
- Frequency 50/60Hz

### 2 - Output data

- Test current 5 mA DC – 50 A DC
- Measuring range / Resolution
- 0,1  $\mu\Omega$  - 999,9  $\mu\Omega$  0,1  $\mu\Omega$
- 1,000 m $\Omega$  - 9,999 m $\Omega$  1  $\mu\Omega$
- 10,00 m $\Omega$  - 99,99 m $\Omega$  10  $\mu\Omega$
- 100,0 m $\Omega$  - 999,9 m $\Omega$  0,1 m $\Omega$
- 1,000  $\Omega$  - 99,99  $\Omega$  10 m $\Omega$
- 100  $\Omega$  - 1000  $\Omega$  0,1  $\Omega$
- Typical accuracy  $\pm(0,2\% \text{ rdg} + 0,2\% \text{ FS})$

### 3 - Environmental conditions

- Operating temperature  $-10^{\circ}\text{C} - +55^{\circ}\text{C} / 14^{\circ}\text{F} - +131^{\circ}\text{F}$
- Storage and transportation  $-25^{\circ}\text{C} - +70^{\circ}\text{C} / -13^{\circ}\text{F} - +158^{\circ}\text{F}$
- Humidity 5 % - 95 % relative humidity, non condensing

### 4 - Dimensions and Weight

- Dimensions 198 mm x 255 mm x 380 mm  
7,8 in x 10 in x 15 in  
(W x H x D) without handle
- Weight 8 kg / 17,6 lb
- Mechanical protection IP43

### 5 - Safety Standards

- European standards LVD 2006/95/EC (EN 61010-1)
- International standards IEC 61010-1

### 6 - Electromagnetic Compatibility (EMC)

- CE conformity EMC standard 89/336/EEC
- Emission EN 50081-2, EN 61000-3-2/3
- Interference Immunity EN 50082-2

Specifications are subject to change without notice.



**IBEKO POWER AB**